



Diesel Power Generators for Mobile Units (Mobile Quiet Diesel Series)

- EPA and CSA certified
- Water cooled Diesel Power Generators, integrated radiator in the cabinet (except in RV QD 3200)
- Low noise and vibration
- Microprocessor control
- Excellent noise reduction cabinet
- 120/240V or 120V outputs
- Specially designed for mobile units



QD 3200



Remote panel included with QD 3200



QD 10000



QD 5000



QD 7500

Model		RV QD 3200	QD 5000 - 120	QD 5000	QD 6000	QD 7500	QD 8000	QD 10000	QD 12000
Nominal Power	(kW)	3.2	5	5	6	7.5	8	10	12
Continuous Power	(kW)	2.88	4.5	4.5	5.4	6.75	7.2	9.5	11.4
Voltage	(Vac)	120	120 (FN)	120/240 (FNF)	120	120	120	120 / 240	120 / 240
Current (120 / 240 Vac)	(A)	26.7	41.7/20.8	41.7/20.8	50	62.5	66.6	83.3 / 41.7	100 / 50
Consumption	(liters/hour)								
	100% load	1,4	2,27	2,27	2,65	3,63	3,86	3,8	4,54
	50% load	1,0	1,47	1,47	1,50	2,12	2,31	1,63	1,82
	25% load	0,7	0,95	0,95	0,79	0,79	0,79	0,4	0,4
Noise	(dBA 3m)								
	100% load				69	71	72	68	68
	50% load	68	68	68	65	66	66		
	No load				64	64	64		
Integrated battery chAriger		no	yes	yes	yes	yes	yes	yes	yes
Cooling		Air	Water	Water	Water	Water	Water	Water	Water
Engine		HATZ 1B30V	Kubota Z482	Kubota Z482	Kubota 722	Kubota 722	Kubota 722	Kubota D1703-M	Kubota D1703-M
RPM		1800	2880	2880				1800	1800
Technology		Inverter	Conventional	Conventional	Inverter	Inverter	Inverter	Conventional	Conventional
Dimensions	(mm)								
	Length	766	876	876	923.2	923.2	923.2	1053.6	1053.6
	Height	453	514.7	514.7	565.9	565.9	565.9	685.8	685.8
	Width	439	581.2	581.2	615.4	615.4	615.4	621.1	621.1
Weight	(kg)	93	181	181	190.9	190.9	190.9	370.1	370.1
PAirt #		36927	52086	38745	36950	36951	36846	36845	36844

Note: Power is reduced by 1% for each 5.5°C increase (above 25°C) and reduces 3,5% for each 305m altitude increase (above 152m)