

Pressurization

Model (115 Vac)	40525B	MT500B-81315	PMT200B-81315
Model (240 Vac)		MT500B-81326	PMT200B-81326
Power (W)	90		20
Suggested breaker (A)	15	20	20
Output pressure (psi)	3 - 8	3 - 5	3 - 5
Flow (SLPM)	25	14,2	5,66
Volumetric capacity (ft ³)	0 - 0,9	10 - 120	0,01 - 60
Connection	tube PE 3/8"	tube PE 3/8"	tube PE 3/8"
Weight (shipping) (kg)	12,3	17,7	22
Size (HxWxD) (mm)	584x457x304	264x431x320	559x534x407
Part# (115 Vac)	27756	44867	47456
Part# (240 Vac)	27756	57369	56106

Repair kit for MT500B-81315	AE01K-A0870-001
Weight (shipping) (kg)	0,91
Part#	20223




Pressure Manifold

Model	6600D-2	6600D-4	6600D-6
Output pressure (psi)	0 - 15	0 - 15	0 - 15
Connection / Outputs	tube PE 3/8" / 2	tube PE 3/8" / 4	tube PE 3/8" / 6
Weight (shipping) (kg)	3	4	5
Size (HxWxD) (mm)	165x191x64	165x279x64	165x368x64
Part#	18813	18813	18813



Pressure window

Contact us for the correct specification of the pressure window for your application.



Silica gel refill

Model	52665-3
Weight (shipping) (kg)	0,68
Part#	40330



Polyethylene tubing (PE) 3/8" black

Model	AE01K-D0840-025	AE01K-D0840-050	AE01K-D0840-100	AE01K-D0840-500
Length (ft / m)	25 / 7,62	50 ft / 15,24	100 / 30,48	500 / 152,4
Weight (shipping) (kg)	1,5	3	5	7
Size (HxWxD) (mm)	11x38x11	11x38x11	11x38x11	28x38x36
Part#	48807	53130	45982	41434

M 1/8" NPT connector for PE 3/8" tube

Model	AE01J-A2016-201
Part#	18543

Flex-Twist Flexible Waveguide

Model	F137CCA2	F137CCA3	F137CDS3	F112CCS2	F112CCS5
Length (mm)	600	900	900	600	1200
Frequency range	5,850 - 6,425 GHz	5,850 - 6,425 GHz	5,82 - 8,2 GHz	7,05 - 10 GHz	7,05 - 10 GHz
Attenuation (db/m)	0,30	0,30	0,30	0,40	0,40
Average power (w)	2000	2000	2000	1260	1260
Peak power (kw)	500	500	500	315	315
VSWR	1,03	1,03	1,10	1,10	1,10
Interface 1	CPR137G	CPR137G	CPR137G	CPR112G	CPR112G
Interface 2	CPR137G	CPR137G	CPR137F	CPR112G	CPR112G
Part#	27966	26205	42282	19924	34999

Flex-Twist



Contact us for other Flex-Twist models

Other connection accessories

Elliptical waveguide and interface




Rigid twist 90°




Interface conversion



Elbow H 90°



Elbow E 90°



Contact us for the complete waveguide and accessories line